

Magnetic Damper absorbs vibration from the ground.



GEO-32MD

GEO-28MD

GEO-24MD

Automatic Levels
Magnetic Damper model

GEO-MD *series*

GEO-24MD
Magnification: 24X

GEO-28MD
Magnification: 28X

GEO-32MD
Magnification: 32X

Features

- ❖ Vibration-resistant by magnetic damper
- ❖ Bright and Quality lens
* Aperture of GEO-32MD: **40mm**
- ❖ Compact body (Length: **190mm**)
- ❖ Waterproof & Dustproof **IP54**



Aperture



Circular Level



Peep sight



Fine adjustment

Set Contents



- Auto Level
- Plumb Bob
- Lens Cap
- Adjustment Tools
- Carrying Case

Option

Aluminium Tripod SAT series



Specifications

| | |
|---------------|--------------|
| Full extended | 1,655mm |
| Full closed | 978mm |
| Weight | 3.5kg |
| Tripod Head | 154mm / 66mm |

※Quick clamp: Available

| Code | Model | Remarks |
|--------|--------|---------------|
| 211501 | SAT-OL | Color: Orange |
| 211002 | SAT-YL | Color: Yellow |

Specifications

| Model | | GEO-32MD | GEO-28MD | GEO-24MD |
|----------------|------------------------------------|----------|----------|----------|
| Telescope | Length | 190mm | | |
| | Image | Erect | | |
| | Aperture | 40mm | 30mm | |
| | Magnification | 32X | 28X | 24X |
| | Field of view (100m) | 1°20' | | |
| | Resolution | 3.5" | 4.5" | |
| | Minimum focus | 0.50m | 0.60m | |
| | Accuracy (1km double-run leveling) | ±1.5mm | ±2.0mm | |
| Graduation | Minimum reading | 1° | | |
| Self-leveling | Method | Magnetic | | |
| | Range | ±15' | | |
| Circular level | Sensitivity | 8' / 2mm | | |
| Weight | Body | 1.26kg | | |
| | Case | 0.60kg | | |
| IP | Class | IP54 | | |

| Code | Model | Remarks |
|--------|----------|--------------------|
| 220830 | GEO-24MD | Magnification: 24X |
| 220831 | GEO-28MD | Magnification: 28X |
| 220832 | GEO-32MD | Magnification: 32X |

Myzox Co., Ltd.

401 Yamagoe, Nagakute, Aichi 480-1111 Japan
TEL : +81-561-64-2210 FAX : +81-561-63-7770

www.myzoxjapan.com

Your Local Authorized Myzox Dealer is :